


GSH Series Light & Slim Outdoor Fixed LED Display

Model#: GSH 6/10



Features



Light & Slim
30% lighter than traditional panel.



Waterproof module design
High protection grade.



Simple Installation & Service.
Front & Rear maintenance & installation.



High Brightness, Low Power Consumption
Average power consumption :185W/m².



Multimode splicing
Meet the needs of different applications.



Special Design of Louvers and ribbing in the module face
Maximize LED efficiency, High-contrast surface.

Specification

	Item	GSH6R/GSH6H	GSH10R/GSH10H
Physical Parameter	Pixel Configuration	SMD	SMD
	Pixel Pitch	6.66mm	10mm
	Module Resolution	48*48	32*32
	Module Dimensions	320*320*30mm	320*320*30mm
Cabinet Parameter	Cabinet Material	Aluminum	Aluminum
	Cabinet Thickness	5inch (130mm)	5inch(130mm)
	Density(pixels/Sq.m)	22,500	10,000
Optical Parameter	Color Grayscale(Bit)	14bit	14bit
	Driving Type	1/6 Scan	1/2 Scan
	Signal Transmission	Ethernet/WIFI/4G	Ethernet/WIFI/4G
	Brightness(nit)	6500/8500	6500/8500
	Viewing Angle	160	160
	Vertical Viewing Angle	75	75
	Brightness Adjustment	Auto	Auto
	Electrical Parameter	AC Input Voltage	110V or 208V
Certification		ETL	ETL
Max Poer Consumption		630W/m2	630W/m2
Avg Power Consumption		210W/m2	210W/m2
Operation Specification	Working Temperature	-40 to 70	-40 to 70
	IP Rating	IP65/IP54	IP65/IP54

